



## Safety Data Sheet

Page 1 of 11

LOCTITE 567 LOW STRENGTH THREAD SEALANT known as  
567 50ml MAST Pipe Sealant Auto

SDS No. : 153487

V002.3

Revision: 24.03.2016

printing date: 05.07.2018

### Section 1. Identification of the substance/preparation and of the company/undertaking

**Product name:** LOCTITE 567 LOW STRENGTH THREAD SEALANT known as 567 50ml MAST Pipe Sealant Auto

**Other means of identification:** LOCTITE 567 TB50MLAU

**Product code:** IDH266308

**Recommended use of the chemical and restrictions on use**

**Intended use:** Adhesive

**Identification of manufacturer, importer or distributor**

**Importer:** Henkel Malaysia Sdn Bhd 46th Floor, Menara TM, Jalan Pantai Baharu, 59200 Kuala Lumpur, Malaysia. Phone :+ 603 22461000 Fax : + 60322461188

**E-mail address of person responsible for Safety Data Sheet:** ap-ua-psra.sea@henkel.com

**Emergency information:** FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call CHEMTREC: +1 703-741-5970

### Section 2. Hazards identification

**GHS Classification:**

**Hazard Class**  
Skin sensitizer

**Hazard Category**  
Category 1

**GHS label elements:**

**Hazard pictogram:**



**Signal word:**

Warning

**Hazard statement:**

H317 May cause an allergic skin reaction.

**Precaution:**

**Prevention:**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves.

**Response:**

P302+P352 IF ON SKIN: Wash with plenty of water.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P363 Wash contaminated clothing before reuse.

**Disposal:**

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.



**Section 3. Composition / information on ingredients**

**Substance or Mixture:**  
Mixture

**Declaration of hazardous chemical:**

Hazard component CAS-No.	Content	GHS Classification
Titanium dioxide 13463-67-7	1- 10 %	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	0.1- 1 %	Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2 H319 Skin sensitizer 1 H317 Chronic hazards to the aquatic environment 2 H411
Cumene hydroperoxide 80-15-9	0.1- 1 %	Organic peroxides E H242 Acute toxicity 4; Oral H302 Acute toxicity 3; Inhalation H331 Acute toxicity 4; Dermal H312 Skin corrosion/irritation 1B H314 Specific target organ toxicity - repeated exposure 2 H373 Chronic hazards to the aquatic environment 2 H411
N,N-Diethyl-p-toluidine 613-48-9	0.1- 1 %	Acute toxicity 3; Oral H301 Acute toxicity 3; Inhalation H331 Acute toxicity 3; Dermal H311 Specific target organ toxicity - repeated exposure 2 H373 Chronic hazards to the aquatic environment 3 H412
N,N-dimethyl-o-toluidine 609-72-3	0.1- 1 %	Acute toxicity 3; Oral H301 Acute toxicity 3; Inhalation H331 Acute toxicity 3; Dermal H311 Specific target organ toxicity - repeated exposure 2 H373 Chronic hazards to the aquatic environment 3 H412
1,4-Naphthalenedione 130-15-4	< 0.1 %	Acute toxicity 3; Oral H301 Acute toxicity 1; Inhalation H330 Skin corrosion/irritation 2; Dermal H315 Serious eye damage/eye irritation 2 H319 Skin sensitizer 1; Dermal H317 Specific target organ toxicity - single exposure 3; Inhalation H335 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410

#### Section 4. First aid measures

<b>Inhalation:</b>	Move to fresh air. If symptoms persist, seek medical advice.
<b>Skin contact:</b>	Rinse with running water and soap. Obtain medical attention if irritation persists.
<b>Eye contact:</b>	Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.
<b>Ingestion:</b>	Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.
<b>Indication of immediate medical attention and special treatment needed:</b>	See section: Description of first aid measures

#### Section 5. Fire fighting measures

<b>Suitable extinguishing media:</b>	Foam, extinguishing powder, carbon dioxide.
<b>Specific hazards arising from the chemical:</b>	Do not expose to direct heat.
<b>Special protection equipment and precautions for firefighters:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
<b>Hazardous combustion products:</b>	Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.

#### Section 6. Accidental release measures

<b>Personal precautions:</b>	Ensure adequate ventilation.
<b>Environmental precautions:</b>	Do not let product enter drains.
<b>Clean-up methods:</b>	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

#### Section 7. Handling and storage

<b>Handling:</b>	Use only in well-ventilated areas. Gloves and safety glasses should be worn Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.
<b>Storage:</b>	Keep away from heat and direct sunlight. Keep container in a well ventilated place. Store above 32° F. (0° C) Store below 90°F. (32.2°C)

**Section 8. Exposure controls / personal protection****Components with specific control parameters for workplace:**

TITANIUM DIOXIDE 13463-67-7	<b>Value type</b>	Time Weighted Average (TWA):
	<b>mg/m<sup>3</sup></b>	10
	<b>Remarks</b>	ACGIH
TITANIUM DIOXIDE 13463-67-7	<b>Value type</b>	Time Weighted Average (TWA):
	<b>mg/m<sup>3</sup></b>	10
	<b>Remarks</b>	MY OEL

- Respiratory protection:** Ensure adequate ventilation.  
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area  
Filter type: A (EN 14387)
- Hand protection:** Chemical-resistant protective gloves (EN 374).  
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):  
nitrile rubber (NBR; >= 0.4 mm thickness)  
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):  
nitrile rubber (NBR; >= 0.4 mm thickness)  
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.
- Eye protection:** Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.  
Protective eye equipment should conform to EN166.
- Body protection:** Wear suitable protective clothing.  
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.
- Engineering controls:** Ensure good ventilation/extraction.
- Hygienic measures:** Good industrial hygiene practices should be observed. Do not eat, drink or smoke while working. Wash hands before work breaks and after finishing work.

**Section 9. Physical and chemical properties**

- Appearance:** white  
paste
- Odor:** mild
- Odor threshold (CA):** No data available.
- pH:** Not determined
- Melting point / freezing point:** No data available.
- Specific gravity:** 1.14
- Boiling point:** > 149 °C (> 300.2 °F)
- Flash point:** > 93.3 °C (> 199.94 °F)
- Evaporation rate:** No data available.

<b>Flammability (solid, gas):</b>	No data available.
<b>Lower explosive limit:</b>	No data available.
<b>Upper explosive limit:</b>	No data available.
<b>Vapor pressure:</b>	< 27 mbar
(; 27 °C (80.6 °F)no method; 50 °C (122 °F))	< 300 mbar
<b>Vapor density:</b>	No data available.
<b>Density:</b>	1.14 g/cm <sup>3</sup>
<b>Solubility:</b>	No data available.
<b>Partition coefficient: n-octanol/water:</b>	No data available.
<b>Auto ignition:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.
<b>VOC content:</b>	< 3 %
(2010/75/EC)	

### Section 10. Stability and reactivity

<b>Reactivity/Incompatible materials:</b>	Acids. Oxidizers. Alkali metals Reaction with reducing agents. Free radical initiators. Peroxides.
<b>Chemical stability:</b>	Stable under recommended storage conditions.
<b>Conditions to avoid:</b>	Protect from direct sunlight.
<b>Hazardous decomposition products:</b>	carbon oxides.

### Section 11. Toxicological information

<b>Oral toxicity:</b>	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method
<b>Inhalative toxicity:</b>	Acute toxicity estimate (ATE) : > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
<b>Dermal toxicity:</b>	Acute toxicity estimate (ATE) : > 2,000 mg/kg Method: Calculation method

Symptoms of Overexposure: May cause an allergic skin reaction.  
Prolonged or repeated contact may cause eye irritation.

**Acute oral toxicity:**

Titanium dioxide 13463-67-7	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	Not specified
Cumene hydroperoxide 80-15-9	Value type	LD50
	Value	550 mg/kg
	Species	rat
	Method	

**Acute inhalative toxicity:**

Titanium dioxide 13463-67-7	Value type	LC50
	Value	> 6.82 mg/l
	Exposure time	4 h
	Species	rat
	Method	

**Acute dermal toxicity:**

Titanium dioxide 13463-67-7	Value type	LD50
	Value	>= 10,000 mg/kg
	Species	hamster
	Method	
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	LD50
	Value	23,000 mg/kg
	Species	rabbit
	Method	

**Skin corrosion/irritation:**

Titanium dioxide 13463-67-7	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	slightly irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Cumene hydroperoxide 80-15-9	Result	corrosive
	Exposure time	
	Species	rabbit
	Method	Draize Test

**Serious eye damage/irritation:**

Titanium dioxide 13463-67-7	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	not irritating
	Exposure time	
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

Titanium dioxide 13463-67-7	Result	not sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	sensitising
	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

**Germ cell mutagenicity:**

Titanium dioxide 13463-67-7	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	Result	negative
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	Result	negative
	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	Result	negative
	Type of study / Route of administration	oral: gavage
	Metabolic activation / Exposure time	
	Species	rat
	Method	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	negative
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	
	Method	OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	Result	positive
	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	Result	negative
	Type of study / Route of administration	dermal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	

**Repeated dose toxicity:**

Titanium dioxide 13463-67-7	Result	NOAEL=24,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	29 ddaily
	Species	rat
	Method	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Cumene hydroperoxide 80-15-9	Result	
	Route of application	inhalation: aerosol
	Exposure time / Frequency of treatment	6 h/d5 d/w
	Species	rat
	Method	

**Section 12. Ecological information**



**Ecotoxicity:**

Do not empty into drains / surface water / ground water.

**Toxicity:**

Titanium dioxide 13463-67-7	Value type	LC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	48 h
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Titanium dioxide 13463-67-7	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	Value type	EC0
	Value	> 10,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	24 h
	Species	
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	LC50
	Value	1.75 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss (reported as Salmo gairdneri)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	EC50
	Value	9.4 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	2.4 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	Value type	LC50
	Value	3.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	Value type	EC50
	Value	18 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	Value type	ErC50
	Value	3.1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchnerella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	Value type	EC10
	Value	70 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	
	Method	
1,4-Naphthalenedione 130-15-4	Value type	EC50
	Value	0.011 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Dunaliella bioculata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)

**Persistence and degradability:**

Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	
	Route of application	aerobic
	Degradability	5 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Cumene hydroperoxide 80-15-9	Result	
	Route of application	no data
	Degradability	0 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,4-Naphthalenedione 130-15-4	Result	
	Route of application	no data
	Degradability	0 - 60 %
	Method	OECD 301 A - F

**Bioaccumulative potential / Mobility in soil:**

Cumene hydroperoxide 80-15-9	Bioconcentration factor (BCF)	9.1
	Exposure time	
	Species	calculation
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Cumene hydroperoxide 80-15-9	LogKow	2.16
	Temperature	
	Method	
1,4-Naphthalenedione 130-15-4	LogKow	1.71
	Temperature	
	Method	

**Section 13. Disposal considerations**

**Product**

**Method of disposal:** Dispose of in accordance with local and national regulations.  
Contribution of this product to waste is very insignificant in comparison to article in which it is used

**Packaging**

**Disposal of uncleaned packages:** After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.  
Disposal must be made according to official regulations.

**Section 14. Transport information**

**General information:**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### Section 15. Regulatory information

**Regulatory Information:** Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 [P.U.(A) 310/213]  
Industry Code of Practice on Chemicals Classification and Hazard Communication

**Global inventory status:**

Regulatory list	Notification
TSCA	yes
AICS	yes
DSL	yes
KECI (KR)	yes
PICCS (PH)	yes
IECSC	yes
NZIOC	yes

### Section 16. Other information

**Disclaimer:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.